

Package: MSG (via r-universe)

October 22, 2024

Type Package

Title Data and Functions for the Book Modern Statistical Graphics

Version 0.8.1

Description A companion to the Chinese book ``Modern Statistical Graphics''.

License GPL

Depends R (>= 3.5.0)

Imports RColorBrewer (>= 1.1.2)

Suggests animation (>= 2.6), igraph (>= 1.2.4.1), KernSmooth (>= 2.23.15), maps (>= 3.3.0), mvtnorm (>= 1.0.11), rgl (>= 0.100.30), RgoogleMaps (>= 1.4.4), plotrix (>= 3.7.6), ggplot2 (>= 3.2.1), grid (>= 3.6.0), sna (>= 2.4)

URL <https://github.com/yihui/MSG>

BugReports <https://github.com/yihui/MSG/issues>

Encoding UTF-8

RoxygenNote 7.1.1

Repository <https://yihui.r-universe.dev>

RemoteUrl <https://github.com/yihui/msg>

RemoteRef HEAD

RemoteSha 8693859ef41139a43e32aeec33ab2af700037f82

Contents

MSG-package	2
andrews_curve	2
assists	3
BinormCircle	4
canabalt	5
char_gen	5
ChinaLifeEdu	6

cut_plot	7
Export.USCN	7
gov.cn.pct	8
heart_curve	9
msg	10
murcia	11
music	11
PlantCounts	12
quake6	12
t.diff	13
tukeyCount	14
tvearn	15
vec2col	15

Index 17

MSG-package	<i>Modern Statistical Graphics</i>
-------------	------------------------------------

Description

Datasets and functions for the Chinese book “Modern Statistical Graphics”.

Author(s)

Yihui Xie <<https://yihui.org>>

andrews_curve	<i>Draw Andrew's Curve</i>
---------------	----------------------------

Description

This function evaluates the transformation of the original data matrix for t from $-\pi$ to π , and uses `matplot` to draw the curves.

Usage

```
andrews_curve(
  x,
  n = 101,
  type = "l",
  lty = 1,
  lwd = 1,
  pch = NA,
  xlab = "t",
  ylab = "f(t)",
  ...
)
```

Arguments

x a data frame or matrix
n number of x-axis values at which f(t) is evaluated
type, lty, lwd, pch, xlab, ylab, ...
passed to [matplot](#)

Value

a matrix of coefficients for each observation at different t values

Author(s)

Yihui Xie <<https://yihui.org>>

References

https://en.wikipedia.org/wiki/Andrews_plot

See Also

[matplot](#)

Examples

```
andrews_curve(iris[, -5], col = as.integer(iris[, 5]))
```

assists

Assists between players in CLE and LAL

Description

The players in the rows assisted the ones in the columns.

References

<http://www.basketballgeek.com/data/>

Examples

```
data(assists)

if (require("sna")) {
  set.seed(2011)
  gplot(assists, displaylabels = TRUE, label.cex = 0.7)
}
```

 BinormCircle

Random numbers containing a “circle”

Description

The data was generated from two independent random variables (standard Normal distribution) and further points on a circle were added to the data. The order of the data was randomized.

Format

A data frame with 20000 observations on the following 2 variables.

V1 the first random variable with the x-axis coordinate of the circle

V2 the second random variable with the y-axis coordinate of the circle

Details

See the example section for the code to generate the data.

Source

<https://yihui.org/en/2008/09/to-see-a-circle-in-a-pile-of-sand/>

Examples

```
data(BinormCircle)

## original plot: cannot see anything
plot(BinormCircle)

## transparent colors (alpha = 0.1)
plot(BinormCircle, col = rgb(0, 0, 0, 0.1))

## set axes limits
plot(BinormCircle, xlim = c(-1, 1), ylim = c(-1, 1))

## small symbols
plot(BinormCircle, pch = ".")

## subset
plot(BinormCircle[sample(nrow(BinormCircle), 1000), ])

## 2D density estimation
library(KernSmooth)
fit = bkde2D(as.matrix(BinormCircle), dpik(as.matrix(BinormCircle)))
# perspective plot by persp()
persp(fit$x1, fit$x2, fit$fhat)

if (interactive() && require("rgl")) {
```

```

# perspective plot by OpenGL
rgl.surface(fit$x1, fit$x2, fit$fhat)
# animation
M = par3d("userMatrix")
play3d(par3dinterp(userMatrix = list(M, rotate3d(M, pi/2, 1, 0, 0), rotate3d(M,
  pi/2, 0, 1, 0), rotate3d(M, pi, 0, 0, 1))), duration = 20)
}

## data generation
x1 = rnorm(10000)
y1 = rnorm(10000)
x2 = rep(0.5 * cos(seq(0, 2 * pi, length = 500)), 20)
y2 = rep(0.5 * sin(seq(0, 2 * pi, length = 500)), 20)
x = cbind(c(x1, x2), c(y1, y2))
BinormCircle = as.data.frame(round(x[sample(20000), ], 3))

```

canabalt

The scores of the game Canabalt from Twitter

Description

The scores of the game Canabalt from Twitter

References

<http://www.neilkodner.com/2011/02/visualizations-of-canabalt-scores-scraped-from-twitter/>
(the URL is not longer accessible)

Examples

```

library(ggplot2)
data(canabalt)
print(qplot(device, score, data = canabalt))
print(qplot(reorder(death, score, median), score, data = canabalt, geom = "boxplot") +
  coord_flip())

```

char_gen

Generate a matrix of similar characters

Description

This function prints a matrix of characters which are very similar to each other.

Usage

```
char_gen(x = c("V", "W"), n = 300, nrow = 10)
```

Arguments

x a character vector of length 2 (usually two similar characters)
 n the total number of characters in the matrix
 nrow the number of rows

Value

a character matrix on the screen

Author(s)

Yihui Xie <<https://yihui.org>>

Examples

```
char_gen()
char_gen(c("0", "Q"))
```

ChinaLifeEdu	<i>Life Expectancy and the Number of People with Higher Education in China (2005)</i>
--------------	---

Description

This data contains the life expectancy and number of people with higher education in the 31 provinces and districts in China (2005).

Format

A data frame with 31 observations on the following 2 variables.

Life.Expectancy Life expectancy

High.Edu.NO Number of people with higher education

Source

China Statistical Yearbook 2005. National Bureau of Statistics.

Examples

```
data(ChinaLifeEdu)
x = ChinaLifeEdu
plot(x, type = "n", xlim = range(x[, 1]), ylim = range(x[, 2]))
u = par("usr")
rect(u[1], u[3], u[2], u[4], col = "antiquewhite", border = "red")
library(KernSmooth)
est = bkde2D(x, apply(x, 2, dpik))
contour(est$x1, est$x2, est$fhat, nlevels = 15, col = "darkgreen", add = TRUE,
        vfont = c("sans serif", "plain"))
```

cut_plot	<i>Cut the points in a scatter plot into groups according to x-axis</i>
----------	---

Description

This function can categorize the variable on the x-axis into groups and plot the mean values of y. The purpose is to show the arbitrariness of the discretization of data.

Usage

```
cut_plot(x, y, breaks, ..., pch.cut = 20)
```

Arguments

x	the x variable
y	the y variable
breaks	the breaks to cut the x variable
...	other arguments to be passed to <code>plot.default</code>
pch.cut	the point symbol to denote the mean values of y

Author(s)

Yihui Xie <<https://yihui.org>>

Examples

```
x = rnorm(100)
y = rnorm(100)
cut_plot(x, y, seq(min(x), max(x), length = 5))
```

Export.USCN	<i>Export of US and China from 1999 to 2004 in US dollars</i>
-------------	---

Description

Export of US and China from 1999 to 2004 in US dollars

Format

A data frame with 13 observations on the following 3 variables.

Export amount of export

Year year from 1999 to 2004

Country country: US or China

Source

https://www.wto.org/english/res_e/statis_e/statis_e.htm

Examples

```
data(Export.USCN)
par(mar = c(4, 4.5, 1, 4.5))
plot(1:13, Export.USCN$Export, xlab = "Year / Country", ylab = "US Dollars ($10^16)",
     axes = FALSE, type = "h", lwd = 10, col = c(rep(2, 6), NA, rep(4, 6)), lend = 1,
     panel.first = grid())
xlabel = paste(Export.USCN$Year, "\n", Export.USCN$Country)
xlabel[7] = ""
xlabel
abline(v = 7, lty = 2)
axis(1, at = 1:13, labels = xlabel, tick = FALSE, cex.axis = 0.75)
axis(2)
(ylabel = pretty(Export.USCN$Export * 8.27))
axis(4, at = ylabel/8.27, labels = ylabel)
mtext("Chinese RMB", side = 4, line = 2)
box()
```

gov.cn.pct

Percentage data in some government websites

Description

This data was collected from Google by searching for percentages in some government websites.

Format

A data frame with 10000 observations on the following 4 variables.

percentage a numeric vector: the percentages

count a numeric vector: the number of webpages corresponding to a certain percentage

round0 a logical vector: rounded to integers?

round1 a logical vector: rounded to the 1st decimal place?

Details

We can specify the domain when searching in Google. For this data, we used 'site:gov.cn', e.g. to search for '87.53% site:gov.cn'.

Source

Google (date: 2009/12/17)

Examples

```

data(gov.cn.pct)
pct.lowess = function(cond) {
  with(gov.cn.pct, {
    plot(count ~ percentage, pch = ifelse(cond, 4, 20), col = rgb(0:1,
      0, 0, c(0.04, 0.5))[cond + 1], log = "y")
    lines(lowess(gov.cn.pct[cond, 1:2], f = 1/3), col = 2, lwd = 2)
    lines(lowess(gov.cn.pct[!cond, 1:2], f = 1/3), col = 1, lwd = 2)
  })
}
par(mar = c(3.5, 3.5, 1, 0.2), mfrow = c(2, 2))
with(gov.cn.pct, {
  plot(percentage, count, type = "l", panel.first = grid())
  plot(percentage, count, type = "l", xlim = c(10, 11), panel.first = grid())
  pct.lowess(round0)
  pct.lowess(round1)
})
if (interactive()) {
  devAskNewPage(ask = TRUE)

  with(gov.cn.pct, {
    plot(count ~ percentage, type = "l")
    grid()

    devAskNewPage(ask = FALSE)

    for (i in 0:99) {
      plot(count ~ percentage, type = "l", xlim = i + c(0, 1),
        panel.first = grid())
    }

    devAskNewPage(ask = TRUE)

    plot(count ~ percentage, pch = 20, col = rgb(0:1, 0, 0, c(0.07,
      1))[round0 + 1], log = "y")
    lines(lowess(gov.cn.pct[round0, 1:2], f = 1/3), col = "red",
      lwd = 2)
    lines(lowess(gov.cn.pct[!round0, 1:2], f = 1/3), col = "black",
      lwd = 2)

    plot(count ~ percentage, pch = 20, col = rgb(0:1, 0, 0, c(0.07,
      1))[round1 + 1], log = "y")
    lines(lowess(gov.cn.pct[round1, 1:2], f = 1/3), col = "red",
      lwd = 2)
    lines(lowess(gov.cn.pct[!round1, 1:2], f = 1/3), col = "black",
      lwd = 2)
  })
}

```

Description

Calculate the coordinates of a heart shape and draw it with a polygon.

Usage

```
heart_curve(n = 101, ...)
```

Arguments

`n` the number of points to use when calculating the coordinates of the heart shape
`...` other arguments to be passed to `polygon`, e.g. the color of the polygon (usually red)

Author(s)

Yihui Xie <<https://yihui.org>>

Examples

```
heart_curve()  
heart_curve(col = "red")  
heart_curve(col = "pink", border = "red")
```

msg

Plot a graph with a pre-installed R script

Description

Plot a graph with a pre-installed R script

Usage

```
msg(fig = "3.6", show_code = TRUE, print_plot = TRUE, filter = 0)
```

Arguments

`fig` Character. The figure number or the R script name, which is given in the book.
`show_code` Logical. TRUE means the codes are shown in the console.
`print_plot` Logical. TRUE means the graph is printed.
`filter` Integer. The line numbers indicating which lines in the code are displayed (when positive) or hidden (when negative).

Value

A graph and the source code

Examples

```
# msg('3.6') msg('ChinaPop')
```

murcia

Composition of Soil from Murcia Province, Spain

Description

The proportions of sand, silt and clay in soil samples are given for 8 contiguous sites. The sites extended over the crest and flank of a low rise in a valley underlain by marl near Albudeite in the province of Murcia, Spain. The sites were small areas of ground surface of uniform shape internally and delimited by relative discontinuities externally. Soil samples were obtained for each site at 11 random points within a 10m by 10m area centred on the mid-point of the site. All samples were taken from the same depth. The data give the sand, silt and clay content of each sample, expressed as a percentage of the total sand, silt and clay content.

References

<http://www.statsci.org/data/general/murcia.html>

Examples

```
data(murcia)
boxplot(sand ~ site, data = murcia)
```

music

Attributes of some music clips

Description

Attributes of some music clips

References

Cook D, Swayne DF (2007). *Interactive and Dynamic Graphics for Data Analysis With R and GGobi*. Springer. ISBN 978-0-387-71761-6.

Examples

```
data(music)
```

PlantCounts	<i>Number of plants corresponding to altitude</i>
-------------	---

Description

For each altitude, the number of plants is recorded.

Format

A data frame with 600 observations on the following 2 variables.

altitude altitude of the area

counts number of plants

Source

<https://cosx.org/2008/11/lowess-to-explore-bivariate-correlation-by-yihui>

Examples

```
## different span for LOWESS
data(PlantCounts)
par(las = 1, mar = c(4, 4, 0.1, 0.1), mgp = c(2.2, 0.9, 0))
with(PlantCounts, {
  plot(altitude, counts, pch = 20, col = rgb(0, 0, 0, 0.5), panel.first = grid())
  for (i in seq(0.01, 1, length = 70)) {
    lines(lowess(altitude, counts, f = i), col = rgb(0, i, 0), lwd = 1.5)
  }
})
```

quake6	<i>Earth quakes from 1973 to 2010</i>
--------	---------------------------------------

Description

The time, location and magnitude of all the earth quakes with magnitude being greater than 6 since 1973.

References

<https://d.cosx.org/d/101510>

Examples

```
data(quake6)
library(ggplot2)
qplot(year, month, data = quake6) + stat_sum(aes(size = ..n..)) + scale_size(range = c(1,
10))
```

t.diff	<i>The differences of P-values in t test assuming equal or unequal variances</i>
--------	--

Description

Given that the variances of two groups are unequal, we compute the difference of P-values assuming equal or unequal variances respectively by simulation.

Format

A data frame with 1000 rows and 99 columns.

Details

See the Examples section for the generation of this data.

Source

By simulation.

References

Welch B (1947). "The generalization of Student's problem when several different population variances are involved." *Biometrika*, 34(1/2), 28–35.

Examples

```
data(t.diff)
boxplot(t.diff, axes = FALSE, xlab = expression(n[1]))
axis(1)
axis(2)
box()

## reproducing the data
if (interactive()) {
  set.seed(123)
  t.diff = NULL
  for (n1 in 2:100) {
    t.diff = rbind(t.diff, replicate(1000, {
      x1 = rnorm(n1, mean = 0, sd = runif(1, 0.5, 1))
      x2 = rnorm(30, mean = 1, sd = runif(1, 2, 5))
      t.test(x1, x2, var.equal = TRUE)$p.value - t.test(x1, x2,
        var.equal = FALSE)$p.value
    })))
  }
  t.diff = as.data.frame(t(t.diff))
  colnames(t.diff) = 2:100
}
```

 tukeyCount

Results of a Simulation to Tukey's Fast Test

Description

For the test of means of two samples, we calculated the P-values and recorded the counts of Tukey's rule of thumb.

Format

A data frame with 10000 observations on the following 3 variables.

pvalue.t P-values of t test

pvalue.w P-values of Wilcoxon test

count Tukey's counts

Details

See the reference for details.

Source

Simulation; see the Examples section below.

References

D. Daryl Basler and Robert B. Smawley. Tukey's Compact versus Classic Tests. *The Journal of Experimental Education*, Vol. 36, No. 3 (Spring, 1968), pp. 86-88

Examples

```
data(tukeyCount)

## does Tukey's rule of thumb agree with t test and Wilcoxon test?
with(tukeyCount, {
  ucount = unique(count)
  stripchart(pvalue.t ~ count, method = "jitter", jitter = 0.2, pch = 19,
    cex = 0.7, vertical = TRUE, at = ucount - 0.2, col = rgb(1, 0, 0, 0.2),
    xlim = c(min(count) - 1, max(count) + 1), xaxt = "n", xlab = "Tukey Count",
    ylab = "P-values")
  stripchart(pvalue.w ~ count, method = "jitter", jitter = 0.2, pch = 21,
    cex = 0.7, vertical = TRUE, at = ucount + 0.2, add = TRUE, col = rgb(0,
    0, 1, 0.2), xaxt = "n")
  axis(1, unique(count))
  lines(sort(ucount), tapply(pvalue.t, count, median), type = "o", pch = 19,
    cex = 1.3, col = "red")
  lines(sort(ucount), tapply(pvalue.w, count, median), type = "o", pch = 21,
    cex = 1.3, col = "blue", lty = 2)
  legend("topright", c("t test", "Wilcoxon test"), col = c("red", "blue"),
```

```

      pch = c(19, 21), lty = 1:2, bty = "n", cex = 0.8)
    })

    if (interactive()) {

      ## this is how the data was generated
      set.seed(402)
      n = 30
      tukeyCount = data.frame(t(replicate(10000, {
        x1 = rweibull(n, runif(1, 0.5, 4))
        x2 = rweibull(n, runif(1, 1, 5))
        c(t.test(x1, x2)$p.value, wilcox.test(x1, x2)$p.value, with(rle(rep(0:1,
          each = n)[order(c(x1, x2)])), ifelse(head(values, 1) == tail(values,
            1), 0, sum(lengths[c(1, length(lengths))])))
        })))
      colnames(tukeyCount) = c("pvalue.t", "pvalue.w", "count")

    }

```

tvearn

Top TV earners

Description

The pay per episode for actors as well as other information.

References

<https://flowingdata.com/2011/02/15/visualize-this-tvs-top-earners/>

Examples

```

data(tvearn)
plot(pay ~ rating, data = tvearn)
library(ggplot2)
qplot(pay, data = tvearn, geom = "histogram", facets = gender ~ ., binwidth = 20000)
qplot(rating, pay, data = tvearn, geom = c("jitter", "smooth"), color = type)

```

vec2col

Generate colors from a vector

Description

This functions generates a color vector from an input vector, which can be of the class numeric or factor.

Usage

```
vec2col(vec, n, name)

## Default S3 method:
vec2col(vec, n, name)

## S3 method for class 'factor'
vec2col(vec, n, name)
```

Arguments

vec	the numeric or factor vector
n	the number of colors to be generated from the palette
name	the name of the palette

Value

a vector of colors corresponding to the input vector

Author(s)

Yihui Xie <<https://yihui.org>>

Examples

```
## convert factor to colors
with(iris, plot(Petal.Length, Petal.Width, col = vec2col(Species), pch = 19))

# another palette
with(iris, plot(Petal.Length, Petal.Width, col = vec2col(Species, name = "Dark2"),
  pch = 19))

## turn numeric values to colors
with(iris, plot(Petal.Length, Petal.Width, col = vec2col(Petal.Width), pch = 19))
```

Index

* package

MSG-package, 2

andrews_curve, 2

assists, 3

BinormCircle, 4

canabalt, 5

char_gen, 5

ChinaLifeEdu, 6

cut_plot, 7

Export.USCN, 7

gov.cn.pct, 8

heart_curve, 9

matplotlib, 3

MSG (MSG-package), 2

msg, 10

MSG-package, 2

murcia, 11

music, 11

PlantCounts, 12

plot.default, 7

polygon, 10

quake6, 12

t.diff, 13

tukeyCount, 14

tvearn, 15

vec2col, 15